



SDS4215E SERIES ~ **New Products**



RoHS Compliant


Low Profile Shielded Power Inductors

PART NUMBERING SYSTEM

SDS	4215E	—	100M	—	LF
TYPE	DIMENSIONS		INDUCTANCE		LEAD FREE

SHAPES AND DIMENSIONS


UNIT : mm




A=4.4 Max. B=4.4 Max. C=1.2 Typ. D=1.60 Max

RECOMMENDED PATTERNS

UNIT : mm



G=1.4 H=4.6 I=1.6



J=1.4 K=5.20 L=2.4 M=1.5

FEATURES

- **Compact, Low profile shielded power inductor** – only **1,60 mm** high, **4.4 mm** square
- Ideal for **high-density applications**
- **Flat bottom surface ensure secure , reliable mounting .**
- Handles **current up to 3.4 Amps!**
- **RoHS-compliant.** 260°C compatible.



SDS4215E SERIES ~ **New Products**



RoHS Compliant

Low Profile Shielded Power Inductors

SPECIFICATION TABLE

PART NUMBER	INDUCTANCE (μ H)	DCR (Ω) (Max.)	Isat (A)	Irms (A) @ 25°C Rise	TEST FREQ. (f)
SDS4215E-1R0N-LF	1.0 \pm 30%	0.048	3.00	2.40	1KHz/1V
SDS4215E -1R2N-LF	1.2 \pm 30%	0.052	2.80	2.34	1KHz/1V
SDS4215E -1R5N-LF	1.5 \pm 30%	0.060	2.60	2.30	1KHz/1V
SDS4215E -1R8N-LF	1.8 \pm 30%	0.066	2.30	2.10	1KHz/1V
SDS4215E -2R2N-LF	2.2 \pm 30%	0.085	2.20	2.00	1KHz/1V
SDS4215E -2R7N-LF	2.7 \pm 30%	0.094	2.00	1.60	1KHz/1V
SDS4215E -3R3N-LF	3.3 \pm 30%	0.105	2.00	1.60	1KHz/1V
SDS4215E-3R9N-LF	3.9 \pm 30%	0.120	1.80	1.50	1KHz/1V
SDS4215E-4R7N-LF	4.7 \pm 30%	0.165	1.60	1.40	1KHz/1V
SDS4215E-5R6N-LF	5.6 \pm 30%	0.177	1.46	1.20	1KHz/1V
SDS4215E-6R8N-LF	6.8 \pm 30%	0.204	1.40	1.15	1KHz/1V
SDS4215E-8R2N-LF	8.2 \pm 30%	0.234	1.28	1.10	1KHz/1V
SDS4215E-100M-LF	10 \pm 20%	0.274	1.16	1.02	1KHz/1V
SDS4215E-120M-LF	12 \pm 20%	0.330	1.08	0.90	1KHz/1V
SDS4215E-150M-LF	15 \pm 20%	0.408	0.86	0.72	1KHz/1V
SDS4215E-180M-LF	18 \pm 20%	0.456	0.82	0.68	1KHz/1V
SDS4215E-220M-LF	22 \pm 20%	0.594	0.74	0.65	1KHz/1V
SDS4215E-270M-LF	27 \pm 20%	0.882	0.70	0.55	1KHz/1V
SDS4215E-330M-LF	33 \pm 20%	1.068	0.58	0.48	1KHz/1V
SDS4215E-390M-LF	39 \pm 20%	1.200	0.56	0.42	1KHz/1V
SDS4215E-470M-LF	47 \pm 20%	1.380	0.52	0.35	1KHz/1V

- Inductance tested at 1kHz, 1 Vrms, 0 Adc using an Agilent/HP 4284A LCR meter or equivalent.
- Isat : DC current at which the inductance drops 35% (typ) from its value without current.
- Irms: Current that causes the specified temperature rise from 25°C ambient.
- Electrical specifications at 25°C.
- Packing Qty 1,000pcs with 7' reel (178mm)